

HDGrip-SoftSkid™

Product Description

HDGrip-SoftSkid™ is a micronized polymer additive that is useful in helping to create a cleanable, non-skid surface when introduced into a topical sealer of appropriate thickness. It is available in Ultra-Fine, Fine and Coarse Grades. Unlike many anti-skid additives this product is less abrasive to bare skin and is cleanable.

Features and Benefits

- Ability to be mixed into sealer or coating with minimum slump
- Useful in acrylics, paints, epoxies, urethanes and polyureas
- Three grades offer user friendly selection
- Cleanable and will not shred your mop*
- Transparent for successful clear sealer applications
- Non-hazardous for easy disposal
- 100% GREEN recycled product

Recommended Applications

HDGrip-SoftSkid™ is recommended for all new and old interior/exterior concrete surfaces requiring a non-skid additive. Product should be mixed well into the sealer/coating. Suggested applications:

Ultra-Fine: areas with less exposure to wet or oily conditions or thinner sealers (acrylics)

Fine: areas subject to intermittent wet or oily conditions (urethanes, polyureas, thin-mil epoxies)

Coarse: areas subject to frequent wet/oily conditions or incline/decline slopes (urethanes, polyureas, thin-mil epoxies)

Coverage Rates

Coverage and grade choice is ultimately the responsibility of the end-user. Coverage is affected by sealer thickness and number of coats applied. We strongly recommend the user makes a test patch and tests for optimum results before opening area up to traffic.

Coverage (by volume)

3.2 ounces of soft-skid per gallon of sealer or approx. 1/5th of a 16 oz. container

16 ounces of soft-skid per 5 gallon unit of sealer

Shelf-Life

This product has an unlimited shelf life in an unopened container. Protect from freezing or extreme heat.

Packaging

8 oz. bottle**, 16 oz. jar, 50 lb. box.

Available as a private-labeled product, contact us for more details.

*coarse grade may prove harder to keep clean and may harm some mop pads

**only available in 300 sq ft HD Garage Kit.



Instructions for Use

HDGrip-SoftSkid™ can be added to create the desired COF (coefficient of friction). Testing for optimum COF is the user's responsibility and we strongly recommend that this be done prior to opening for traffic.

Using a mixing-wand attached to a cordless drill, the user should start the mixing process on a slow or low speed (higher speeds can introduce air into some sealers). The **HDGrip-SoftSkid™** can now be introduced slowly into the sealer (dumping the sealer can cause clumps). Once the product is fully distributed the sealer can be applied via brush or roller.

It is important to note that this product can sink to the bottom of your roller pan or bucket over time. It is important to allow the roller or brush to hit the bottom of the pan or re-mix from time to time in order to keep an even distribution of the product onto the substrate.

Clean-Up

Broom and dust-pan

Product Removal

Once sealer has cured this product can be sanded from the surface if desired.

Precautions and Limitations

Restrict the use of the floor to light traffic and non-harsh chemicals 24 hours has passed.

Test cleaners before using on this product. This product was designed and tested for use on concrete surfaces although it maybe perform equally well on non-concrete surfaces. This product can prove to be a nuisance dust and if in windy or breezy conditions consider protecting yourself with a dust-mask and eye protection.

NOTICE TO BUYER: DISCLAIMER OF WARRANTIES AND LIMITATIONS ON OUR LIABILITY

*We warrant that our product is manufactured to the specifications as stated her or in other publications. All other information supplied by us is accurate to the best of our knowledge. Such information supplied about our products is not a representation or a warranty. It is supplied on the condition that you shall make your own tests to determine the suitability of our product for your particular purpose. **NO WARRANTY IS MADE, EXPRESSED OR IMPLIED, REGARDING SUCH OTHER INFORMATION, THE DATA ON WHICH IT IS BASED, OR THE RESULTS YOU WILL OBTAIN FROM ITS USE. NO WARRANTY IS MADE, EXPRESSED OR IMPLIED, THAT OUR PRODUCT SHALL BE MERCHANTABLE OR THAT OUR PRODUCT SHALL BE FIT FOR ANY PARTICULAR PURPOSE. NO WARRANTY IS MADE THAT THE USE OF SUCH INFORMATION OR OUR PRODUCT WILL NOT INFRINGE UPON ANY PATENT.** We shall have no liability for incidental or consequential damages, direct or indirect. Our liability is limited to the net selling price of our product or the replacement of our product, at our option. Acceptance of delivery of our product means that you have accepted the terms of this warranty whether or not purchase orders or other documents state terms that or other documents state terms that vary from this warranty. No representative is authorized to make any representation or warranty or assume any other liability on our behalf with any sale of our products. Any use or application other than recommended herein is the sole responsibility of the user. Uncured epoxy resins, polymers and their curing agents may be **ALKALINE, TOXIC or BOTH**, depending on the particular system. They may cause **ALLERGIC REACTIONS or HYPERSENSITIVITY REACTIONS.** **BEFORE USING any material, READ THE MATERIAL SAFETY DATA SHEET AND FOLLOW ALL PRECAUTIONS TO PREVENT BODILY HARM.** COPYRIGHT 1/1/11 Legacy Industrial, A Clean Seal LLC Company or Legacy Industrial Corp.*